



Control stations and enclosures

Control stations XAL

For Harmony® XB5 plastic ø22 control and signalling units

Characteristics				
Ambient air temperature around the device	For storage	°C	- 40...+ 70	
	For operation	°C	- 25...+ 70 unless otherwise stated	
Electric shock protection			Conforming to IEC 60536: class II	
Degree of protection			Conforming to IEC 60529: IP 65	
Conformity to standards			EN/IEC 60947-1, EN/IEC 60947-5-1, EN/IEC 60947-5-4, EN/IEC 60947-5-5, EN/IEC 60204-1	
Product certifications	UL Listed, CSA		Standard single contacts with screw clamp terminals: A600; R300 Light blocks with screw clamp terminals	
Material and colours			XAL K; polycarbonate, light grey RAL 7035 and yellow RAL 1021	


Emergency stop					
Description	Type	Type of contact		Reference	Weight kg
					
		N/O	N/C		
1 mushroom head pushbutton, ø 40mm, red Turn release	Standard	—	1	XALK178C (1) (2)	0.202



XALK178C

(1) XALK178C conforms to ASD and HKHA requirements.
(2) XALK178C will be delivered separately as below 4 items.

Empty enclosures			
Description	Number of cut-outs	Reference	Weight kg
Light grey "RAL 7035" base Yellow "RAL 1021" lid For Emergency stop function	1	XALK01	0.136

Head				
Shape of head	Type of reset	Push	Reference	Weight kg
		ø (mm)		
	Turn to release	40	ZB5AS844	0.044
			Red Yellow (body)	



ZB5AS844

Contact Body					
Description	Type of contact	Type of contact		Unit reference	Weight kg
		N/O	N/C		
Contact blocks	Single with body/fixing collar	—	1	ZB5AZ102	0.021



ZB5AZ102

Standard Legend holder			
Description	Lending marking	Reference	Weight kg
With legend (English)	Emergency stop	ZBY2330	0.002

Schneider
Electric

施耐德電氣